

MEMBRANE SYSTEM FOR WATERPROOFING

External & Internal Expansion Joints

25 - 500 mm (1 - 20") Expansion Gaps

Features

Movement

Easy to install

High movement capacity +/- 250mm

Material

1.14mm thick EPDM waterproofing membrane bonded to the substrate and cross-linked to membranes bonded to the side and foot plates of the joint encapsulating the expansion joint

External and Internal Locations

Floor to Floor

Floor to Wall

Wall to Wall

Corner Wall

Roof to Roof

Roof to Wall

Parapet Walls

Traffic Frequency per day



-

-

-

-

-

System Options

Gap width(s)	25-500 mm
Material width(s)	325, 500, 750, 1000mm
Material thickness	1.14mm
Colour(s)	Black (RAL 7021)
Drainage	Down pipe option
Pre-assembly in factory	Contact Vexcolt



Aquatec 1500 : A01-A02

APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets



| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com

| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

www.vexcoltindia.com

Aquatec 1500 : A01-A02

Expansion Joint Selection Criteria

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm)		Watertightness	Dielectric rating	Product Dimensions				Product Number
		±	[Total]			Thickness (mm)	Material Widths (mm)	Sightline A (mm)	Blockout C (mm)	
Floor - Floor	25 - 500	50% Gap	100% Gap	EN1928(B)	2Kv	1.14	325	-	-	1500-A01-325
Floor - Wall							500			1500-A01-500
Wall - Wall							750			1500-A01-750
Corner Wall							1000			1500-A01-1000

