

CONTROL JOINT

Floor to Floor

3 - 7 mm (3/32 - 1/4") Joint Width

Micratec : SE + SV

Features

Surface

Easy transit: Americans with Disabilities Act (ADA) compliant across the entire movement cycle

3mm minimum visible line width between finishes

VAMAC versions of these joints are London Underground Limited 1-085 'Fire Safety Performance of Materials' tested and approved for below ground applications such as metro stations.

Movement

Excellent movement capacity for profile width

Traffic Frequency per day

				
> 25,000	≤ 10,000	≤ 10,000	> 25,000	≤ 1,000

System Options

Sightline width(s)	3, 5, 7 mm
Height(s)	25, 50, 75, 100 mm
Metal type(s)	304-grade Stainless Steel 316-grade Stainless Steel CZ 108 Brass
Seal colour(s)	Black (RAL 7021) Grey (RAL 7038) Beige (RAL 1015)
Fire barrier	Not applicable
Waterproofing	Not applicable
Pre-assembly in factory	Not applicable



APPLICATIONS

Airport Terminals | Educational | Exhibition Centres
Department Stores | Distribution & Retail Warehouses
Factories | Hospitals | Museums | Offices & Hotels
Parking | Places of Worship | Residential Buildings
Rail, Metros & Elevated Rail Stations | Roads & Bridges
Shopping Centres | Sports Stadiums | Supermarkets



| United Kingdom | T : +44 (0) 3707 876 543 | E : info@vexcolt.com | W : www.vexcolt.com

| India | T : +91 9599 291 000 | E : info@vexcoltindia.com | W : www.vexcoltindia.com

www.vexcoltindia.com

CONTROL JOINT

Floor to Floor

3 - 7 mm (3/32 - 1/4") Joint Width

Micratec : SE + SV

Control Joint Selection Criteria

Load Rating

Product Details

Joint Location	Gap Width B (mm)	Movement Capacity (mm)		Eurocode Rating				Product Dimensions		Sightline A (mm)	Blockout C (mm)	Product Number
		±	[Total]					H1 (mm)	H2 (mm)			
Floor - Floor EPDM	-	± 1.0	[2.0]	35 kN	190 kN	30 kN	630 kN	25: 50: 75: 100	-	3	-	SE-003-(H1)
		± 1.5	[3.0]							5		SE-005-(H1)
		± 2.0	[4.0]							7		SE-007-(H1)
Floor - Floor VAMAC	-	± 1.0	[2.0]	35 kN	190 kN	30 kN	630 kN	25: 50: 75: 100	-	3	-	SV-003-(H1)
		± 1.5	[3.0]							5		SV-005-(H1)
		± 2.0	[4.0]							7		SV-007-(H1)

When specifying or ordering please add the **height (H1)** required to the Product Reference.

For example Micratec : SE-005-050 denotes a control joint 50mm high.

When specifying or ordering please select EPDM or VAMAC core colour as black, grey or stone (beige).

